


**SECTION I - IDENTITY**

Product Identity (as used on Label and List): **Epoxy Wood Rebuilder - Part A (Resin)**

Manufacturer's Name and Address: H.F. Staples & Co., Inc.  
9 Webb Drive  
P.O. Box 956  
Merrimack, NH 03054

Emergency Telephone Number: 800-255-3924.  
Telephone Number for Information: 800-682-0034;  
603-889-8600;  
603-883-9409 (fax).



UPC: 0 27046 00401 4 Mfr. #401, net 4 fl.-oz. (with Part B)  
0 27046 00402 1 Mfr. #402, net 8-fl.oz. (with Part B)  
0 27046 00403 8 Mfr. #403, net 16-fl. oz. (with Part B)  
0 27046 00404 5 Mfr. #404, net 1-quart (with Part B)  
0 27046 00405 2 Mfr. #405, net 1-gallon (with Part B)

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

<u>Component</u>	<u>CAS Registration #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits Recommended</u>
Diglycidyl Ether of Bisphenol A	025068-38-6	N/A	N/A	N/A
Diisodecyl Phthalate	26761-40-0	N/A	N/A	N/A

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point: N/A.  
Vapor Pressure (mm Hg.): N/A.  
Vapor Density (AIR=1): N/A.  
Solubility in Water: Insoluble.  
Specific Gravity (H<sub>2</sub>O=1): 0.7.  
Melting Point: N/A.  
Evaporation Rate (Butyl Acetate=1): N/A  
Appearance and Odor: Off-white thixotropic paste, slight odor.

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flashpoint (Method Used): 490°F (closed cup).  
Flammable Limits: Not established.  
LEL: N/A.  
UEL: N/A.  
Extinguishing Media: Carbon dioxide, dry chemical, foam, water spray.  
Special Fire Fighting Procedures: Use self-contained breathing apparatus.  
Unusual Fire and Explosion Hazards: None known.

**SECTION V - REACTIVITY DATA**

Stability: Stable.  
Conditions to Avoid: Excessive heat over long periods of time.  
Incompatibility (Materials to Avoid): Strong oxidizers, acids and bases.  
Hazardous Polymerization: Will not occur.  
Conditions to Avoid: Strong acids or bases.  
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide, aldehydes.

**SECTION VI - HEALTH HAZARD DATA**

Routes of Entry: Inhalation:	Yes.	
	Skin:	Yes.
	Ingestion:	Yes.
Health Hazards (Acute and Chronic):	Moderate skin irritation or sensitization possible. Possible redness of skin, rash, itching, allergy, eczema skin conditions.	
Carcinogenicity:	NTP:	None;
	IARC Monographs:	None;
	OSHA Regulated:	Not regulated.
Signs and Symptoms of Exposure:	Possible irritation, rash, or asthmatic type response in sensitized persons with frequent and prolonged contact with skin.	
Medical Conditions Generally Aggravated by Exposure:	Skin and eye conditions.	
Emergency and First Aid Procedures:	Wash with soap and water, remove contaminated clothing and launder before re-use. Flush eyes with water for 15 minutes. Call Physician.	

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to Be Taken in Case Material Is Released or Spilled:	Use absorbent material to collect for disposal.
Waste Disposal Method:	Dispose in accordance with local, state, and federal regulations.
Precautions to Be Taken in Handling and Storing:	Avoid contact with skin and eyes. Store in cool dry area in closed containers.
Other Precautions:	Keep out of the reach of children.


**SECTION VIII - CONTROL MEASURES**

Respiratory Protection (Specify Type):	Use approved NIOSH dust mask when sanding or sawing. Nuisance dust may be present when sanding or sawing cured material.
Ventilation:	Good general ventilation is sufficient for most conditions.
Local Exhaust:	None needed.
Special:	Not needed.
Mechanical (general):	N/A.
Other:	Use impervious (rubber) gloves.
Protective Gloves:	Wear protective glasses.
Eye Protection:	None needed.
Other Protective Clothing or Equipment:	Keep work area, skin, and clothing clean and free of uncured epoxy.
Work/Hygienic Practices:	

**SECTION I - IDENTITY**

Product Identity (as used on Label and List): **Epoxy Wood Rebuilder - Part B (Hardener)**

Manufacturer's Name and Address: H.F. Staples & Co., Inc.  
9 Webb Drive  
P.O. Box 956  
Merrimack, NH 03054



Emergency Telephone Number: 800-255-3924.  
Telephone Number for Information: 800-682-0034;  
603-889-8600;  
603-883-9409 (fax).

UPC: 0 27046 00401 4 Mfr. #401, net 4 fl.-oz. (with Part A)  
0 27046 00402 1 Mfr. #402, net 8-fl.oz. (with Part A)  
0 27046 00403 8 Mfr. #403, net 16-fl. oz. (with Part A)  
0 27046 00404 5 Mfr. #404, net 1-quart (with Part A)  
0 27046 00405 2 Mfr. #405, net 1-gallon (with Part A)

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

<u>Component</u>	<u>CAS Registration #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits Recommended</u>
Modified Polyamine Hardener	70776-30-6	N/A	N/A	N/A
Diisodecyl Phthalate	26761-40-0	N/A	N/A	N/A

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point: N/A.  
Vapor Pressure (mm Hg.): N/A.  
Vapor Density (AIR=1): N/A.  
Solubility in Water: Insoluble.  
Specific Gravity (H<sub>2</sub>O=1): 0.7.  
Melting Point: N/A.  
Evaporation Rate (Butyl Acetate=1): N/A  
Appearance and Odor: Light brown thixotropic paste, slight amine odor.

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flashpoint (Method Used): Greater than 200°F (closed cup).  
Flammable Limits: Not established.  
LEL: N/A.  
UEL: N/A.  
Extinguishing Media: Carbon dioxide, dry chemical, foam, water spray.  
Special Fire Fighting Procedures: Use self-contained breathing apparatus.  
Unusual Fire and Explosion Hazards: None known.

**SECTION V - REACTIVITY DATA**

Stability: Stable.  
Conditions to Avoid: Excessive heat over long periods of time.  
Incompatibility (Materials to Avoid): Strong oxidizers, acids and bases.  
Hazardous Polymerization: Will not occur.  
Conditions to Avoid: Strong acids or bases.  
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide, aldehydes.

**SECTION VI - HEALTH HAZARD DATA**

Routes of Entry: Inhalation:	Yes.	
	Skin:	Yes.
	Ingestion:	Yes.
Health Hazards (Acute and Chronic):	Moderate skin irritation or sensitization possible. Possible redness of skin, rash, itching, allergy, eczema skin conditions.	
Carcinogenicity:	NTP:	None;
	IARC Monographs:	None;
	OSHA Regulated:	Not regulated.
Signs and Symptoms of Exposure:	Possible irritation, rash, or asthmatic type response in sensitized persons with frequent and prolonged contact with skin.	
Medical Conditions Generally Aggravated by Exposure:	Skin and eye conditions.	
Emergency and First Aid Procedures:	Wash with soap and water, remove contaminated clothing and launder before re-use. Flush eyes with water for 15 minutes. Call Physician.	

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to Be Taken in Case Material Is Released or Spilled:	Use absorbent material to collect for disposal.
Waste Disposal Method:	Dispose in accordance with local, state, and federal regulations.
Precautions to Be Taken in Handling and Storing:	Avoid contact with skin and eyes. Store in cool dry area in closed containers.
Other Precautions:	Keep out of the reach of children.

**SECTION VIII - CONTROL MEASURES**

Respiratory Protection (Specify Type):	Use approved NIOSH dust mask when sanding or sawing. Nuisance dust may be present when sanding or sawing cured material.
Ventilation:	Good general ventilation is sufficient for most conditions.
Local Exhaust:	None needed.
Special:	None needed.
Mechanical (general):	N/A.
Other:	Use impervious (rubber) gloves.
Protective Gloves:	Wear protective glasses.
Eye Protection:	None needed.
Other Protective Clothing or Equipment:	Keep work area, skin, and clothing clean and free of uncured epoxy.
Work/Hygienic Practices:	